



FC-321

FEATURES

- **Inputs** - 2 3G HD-SDI on BNC connectors.
- **Outputs** - 1 HDMI.
- **HDTV Compatible.**
- **Audio Group De-embedded Selection.**
- **Multi-Standard Operation** - SDI (SMPTE 259M and SMPTE 344M), HD-SDI (SMPTE 292M) and 3G HD-SDI (SMPTE 424M).
- **Active Input & Output LED Indicators.**
- **Switching** - Front panel and IR remote (included).
- **Compact DigiTOOLS®** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUTS:	2 SD/HD-SDI, 3G HD-SDI on a BNC connector.
OUTPUT:	1 HDMI connector.
MAX. DATA RATE:	Up to 3Gbps.
STANDARD COMPLIANCE:	HDMI 1.3.
INDICATOR LEDES:	SD/HD, OUT, ON.
POWER SOURCE:	5V DC, 450mA.
DIMENSIONS:	12cm x 7.2cm x 2.4cm (4.7" x 2.8" x 1.0") W, D, H.
WEIGHT:	0.3kg (0.7lbs).
ACCESSORIES:	Power supply.
OPTIONS:	RK-3T 19" rack mount adapter.