



FC-331

FEATURES

- HDTV Compatible.
- Inputs - 3G HD-SDI on a BNC connector.
- Looping Input.
- Outputs - 1 HDMI.
- Audio Group De-embedded Selection.
- Multi-Standard Operation - SDI (SMPTE 259M and SMPTE 344M), HD-SDI (SMPTE 292M) and 3G HD-SDI (SMPTE 424M).
- Active Input & Output LED Indicators.
- Compact DigiTOOLS® - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUT:	1 SD/HD-SDI, 3G HD-SDI on a BNC connector.
OUTPUTS:	1 SD/HD-SDI, 3G HD-SDI loop on a BNC connector, 1 HDMI connector.
MAX. DATA RATE:	Up to 3Gbps.
STANDARD	HDMI 1.3.
COMPLIANCE:	
INDICATOR LEDES:	SD/HD, OUT, ON.
POWER SOURCE:	5V DC, 400mA.
DIMENSIONS:	12cm x 7.2cm x 2.4cm (4.7" x 2.8" x 1.0") W, D, H.
WEIGHT:	0.3kg (0.7lbs).
ACCESSORIES:	Power supply.
OPTIONS:	RK-3T 19" rack adapter.