



VM-2HDMI

FEATURES

- Max. Data Rate - 1.65Gbps.
- HDTV Compatible.
- HDCP Compliant.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances.
- Enhanced EDID (Extended Display Identification Data) - The unit can store and recall a default EDID setting in non-volatile memory from one of the outputs allowing convenient and reliable connection to the source.
- Active Input & Output LED Indicators.
- Compact DigiTOOLS® - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUT:	HDMI connector.
OUTPUTS:	2 HDMI connectors.
BANDWIDTH:	Supports up to 1.65Gbps bandwidth per graphic channel.
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI 1.1 and HDCP.
CONTROLS:	EDID SETUP button.
INDICATOR LEDs:	INPUT, OUT1, OUT2, and POWER LEDs.
POWER SOURCE:	12V DC, 170mA.
DIMENSIONS:	12cm x 7.5cm x 2.5cm (4.7" x 2.95" 0.98") W, D, H.
WEIGHT:	0.3kg (0.67lbs) approx.
ACCESSORIES:	Power supply, bracket installation kit.
OPTIONS:	RK-3T 19" rack adapter.