



## VM-2HDxI

---

### FEATURES

---

- Max. Data Rate - 3Gbps.
- HDTV Compatible.
- Multi-Standard Operation - SDI (SMPTE 259M/344M), HD-SDI (SMPTE 292M) & 3G HD-SDI (SMPTE 424M).
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances.
- HD-SDI & SDI Input Indication LEDs.
- Ultra Compact Pico TOOLS™ - 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-4PT rack adapter.

### TECHNICAL SPECIFICATIONS

---

INPUT: 1 SMPTE-259M/292M/344M/424M serial video, 75Ω on a BNC connector.

OUTPUTS: 2 equalized and reclocked SMPTE-259M/292M/344M/424M outputs 75Ω on BNC connectors.

MAXIMUM DATA RATE: 2.97Gbps.

MAX. OUTPUT LEVEL: 800mVpp/75Ω.

COUPLING: AC.

POWER SOURCE: 12V DC, 250mA.

DIMENSIONS: 6.22cm x 5.24cm x 2.41 cm (2.45" x 2.06" x 0.95") W, D, H.

WEIGHT: 0.14kg (0.31 lbs) approx.

ACCESSORIES: Power supply, mounting bracket.

OPTIONS: RK-4PT 19" rack adapter.