







SPEAKER CABLES

SUPERFLEXIBLE STUDIO SPEAKER CABLES

SPECIFICATIONS AND CHARACTERISTICS

Configuration						
Part No.		2972	3103	3104		
No. of Conductor		4	2	4		
Conductor	Details	7/26/0.12 OFC (bare)		7/50/0.12 OFC (bare)		
	Size	2.05mm ² (#15AWG)		3.96mm ² (#12AWG)		
Insulation Ov. Dia. (mm)		3.2φ(0.126"φ) PVC		4.5φ(0.177"φ) PVC		
Jacket	Ov.Dia. (mm)	10.5φ(0.413"φ)	12.0φ(0.472"φ)	14.5φ(0.571"φ)		
	Material	Flexible PVC, Matte Black				
Weight per 100m (328Ft) roll		17kg	20kg	31kg		
DC Resistance (20°C)		0.0088Ω/m (0.0027Ω/Ft)		0.005Ω/m (0.0015Ω/Ft)		
Inductance (20°C, 1kHz) <small>(Refer to the figures shown in the capacitance data.)</small>	1-2	0.7μH/m (0.21μH/Ft)		0.6μH/m (0.18μH/Ft)		
	1-3	0.7μH/m (0.21μH/Ft)		0.6μH/m (0.18μH/Ft)		
Capacitance (20°C)	Frequency	100Hz	1kHz	10kHz	50kHz	100kHz
2972 	1-2	130pF/m (39.7pF/Ft)	100pF/m (30.5pF/Ft)	81pF/m (24.7pF/Ft)	74pF/m (22.6pF/Ft)	71pF/m (21.7pF/Ft)
	1-3	110pF/m (33.6pF/Ft)	79pF/m (24.1pF/Ft)	63pF/m (19.2pF/Ft)	57pF/m (17.4pF/Ft)	56pF/m (17.1pF/Ft)
3103 	1-2	106pF/m (32.3pF/Ft)	93pF/m (28.4pF/Ft)	83pF/m (25.3pF/Ft)	76pF/m (23.2pF/Ft)	74pF/m (22.6pF/Ft)
3104 	1-2	110pF/m (33.6pF/Ft)	99pF/m (30.2pF/Ft)	86pF/m (26.2pF/Ft)	78pF/m (23.8pF/Ft)	76pF/m (23.2pF/Ft)
	1-3	90pF/m (27.5pF/Ft)	78pF/m (23.8pF/Ft)	67pF/m (20.4pF/Ft)	61pF/m (18.6pF/Ft)	59pF/m (18.0pF/Ft)

COMMON SPECS.

Voltage Breakdown	Must withstand at DC 500V/ 15sec.	
Insulation Resistance	10 ⁴ MΩ · m Minimum at DC 125 V, 20°C	
Emigration of Jacket Material	Non-Emigrant to ABS resin	
Applicable Temperature	-20°C~+70°C(-4°F~ +158°F)	
Roll Sizes	2972	100m (328Ft) /300m (984Ft)
	3103/3104	100m (328Ft) /250m (820 Ft)
Standard	UL13 CL2X 75°C	

Remarks: Connecting the conductors as diagonal pairs greatly reduces mutual inductance, even though cross-talk interference is negligible.