



| Model  | Description  | UK List<br>ex VAT (£)      |
|--|--|----------------------------|
| Radio Consoles<br>3000 Plus Series Base Unit2  |  |                            |
| OXYGEN 3000 PLUS 16F-1AIO  | Digital broadcast console 16 Faders; 5 Mic IN with +48v; 3 bal. stereo IN; 2 USB Audio I/O; 1 Telephone Hybrid; 1 Bluetooth I/O; 1 Telco Audio; GPIO; 4 bal. stereo Out; 1 Digital I/O; 1 Headphones; Streaming I/O. 7" Display. HDMI out. Remote control software.  | 6,030.00                   |
| OXYGEN 3000 PLUS 12F-1AIO  | Digital broadcast console 12 Faders; 5 Mic IN with +48v; 3 bal. stereo IN; 2 USB Audio I/O; 1 Telephone Hybrid; 1 Bluetooth I/O; 1 Telco Audio; GPIO; 4 bal. stereo Out; 1 Digital I/O; 1 Headphones; Streaming I/O. 7" Display. HDMI  | 4,980.00                   |
| OXYGEN 3000 PLUS 8F-1AIO   | out. Remote control software.  Digital broadcast console 8 Faders; 5 Mic IN with +48v; 3 bal. stereo IN; 2 USB Audio I/O; 1 Telephone Hybrid; 1 Bluetooth I/O; 1 Telco Audio; GPIO; 4 bal. stereo Out; 1 Digital I/O; 1 Headphones; Streaming I/O. 7" Display. HDMI out. Remote control software.                                  | 4,200.00                   |
| <b>3000 Plus Series Options</b> OXYGEN 3000 PLUS - AIO Board   | Audio I/O board for Oxygen 3000 Plus - 5 Mic IN with +48v; 3 bal. stereo IN; 2 USB Audio I/O; 1 Telephone Hybrid; 1 Bluetooth I/O; 1 Telco Audio; GPIO; 4 bal. stereo Out; 1 Digital I/O; 1 Headphones (2nd Audio board not compatible with 8-Fader desk)  | 1,055.00                   |
| OXYGEN 3000 PLUS - 16DIO Board<br>OXYGEN 3000 PLUS - 32DIO Board<br>OXYGEN 3000 PLUS - PSU-RID<br><b>2000 Series Base Unit</b> | AoIP DANTE interface 16 IN and 16 OUT mono for Oxygen 3000 Plus AoIP DANTE interface 32 IN and 32 OUT mono for Oxygen 3000 Plus Redundant power supply unit for Oxygen 3000 Plus   | 445.00<br>665.00<br>180.00 |
| OXYGEN 2000-5M-BT  1000 Series Base Units  | Digital broadcast console 12 Faders; 5 Mic IN with +48v; 3 bal. stereo IN; 2 USB Audio I/O; 1 Telephone Hybrid; 1 Bluetooth I/O; 1 Telco Audio; GPIO interface; 4 bal. stereo Out; 1 Digital O; 1 Headphone, audio routing; 8ST In +8ST Out Dante I/O (optional).  | 2,980.00                   |
| OXYGEN 1000-BT   | Digital broadcast console 6 Faders; 3 Mic IN with +48v; 4 bal. stereo IN; 2 USB Audio I/O; 1 Telephone Hybrid; 1 Bluetooth I/O; 1 Telco Audio; GPIO interface;   | 2,195.00                   |
| OXYGEN 1000-BT RACK  | 4 bal. stereo Out; 1 Digital O; 1 Headphone. Dante I/O optional Digital broadcast console rack; 3 Mic IN with +48v; 4 bal. stereo IN; 2 USB Audio I/O; 1 Telephone Hybrid; 1 Bluetooth I/O; 1 Telco Audio; GPIO interface; 4 bal. stereo Out; 1 Digital O; 1 Headphone, audio routing; Remote Control Software. Dante I/O optional | 1,765.00                   |
| 1000/2000 Series Options   |  |                            |
| OXY DANTE-1K-2K  | Dante AoIP interface for Oxygen 1000/2000, 8 stereo IN and 8 stereo OUT. Support for AES67 RTP, SMPTE ST2110-30 RTP.   | 455.00                     |
| Options Compatible with all Radio  |  |                            |
| OXY TALK-BOX   | Talk Box for presenter/guest with mic control on/off button, cough/mute button, tally lamp driver, headphone amplifier, volume control (2x 3.5mm out) and power supply. Compatible with console Oxygen 1000, 2000, 3000.   | 285.00                     |
| OXY 4TALKBOX-SWITCH  | Talk box switcher for Oxygen 1000, 2000 and 3000. It switches up to 4 talk boxes (commands, services and signals) between 2 Oxygen consoles, allowing you to use and share the studio between 2 control rooms.   | 1,320.00                   |





**UK List** Model Description ex VAT (£) **Adapter Cable Set OXY ADPT-SET-8** Adapter set RJ45-XLR for Oxygen 1000/2000/3000P. 8 adapters 1,5m: 2xRJ45-250.00 MIC; 3xRJ45-LINE IN; 1xRJ45-TELCO; 2xRJ45-LINE OUT. 1,5m; 4x SFTP 2m; 4x SFTP cm. **Turnkey Radio Systems** P.O.A. AxelTech have a team of engineers based out of their factory in Bologna who design, build, test and install complete radio studio systems which can be disassembled, shipped and then put together by the customer on-site with minimal effort. **Radio Automation OFFLINE-REC** Software licence OFF-LINE Recorder, audio digital recorder from satellite; 1,070.00 scheduled Start/Stop, GPI commands and VOX: **XRADIO** Radio Automation licence: On Air and Core; Live Assist/Automated Playout 1,915.00 (runtime Playlist Generation by rules), Hotkeys, GPI, Voice-track, Streaming, Live Remoter, Web Presenter Board; Library manager, Clock/Sequence scheduling, Traffic Scheduling, Audio Recorder/Editor. User Right Management. **XRADIO CORE** Radio Automation License: Core module with Library management, 785.00 clock/sequence management and scheduling for real-time playlist generation by rules, advertising scheduling, audio recording/editing. User management. **SPLITPLAYER** Software license SPLIT, 1 channel audio player for 1 comemrcial area 1,045.00 scheduled with RAM-COMM **XRADIO ON-AIR** Radio Automation licence: On Air Playout module with Live Assist/Automated 1,135.00 Playout (runtime playlist generation by rules), Hotkeys, GPI, Voice-track, Streaming, Live Remoter, Web Presenter Board. User Right Management. XRADIO ON-AIR ENTERPRISE Radio Automation licence. On Air Enterprise Playout module with dual screen 1,830.00 UI for advanced Live Assist control including Automated Playout (runtime playlist generation by rules), 4 Hotkeys, GPI, Voice-Track, Streaming, Live Remoter, Web Presenter Board, ect.). User Right Management. XRADIO ON-AIR SMART 480.00 On Air Smart 1 channel License: automatic playout for Radio/WEB, Public Address and audio backup. Combine multiple On Air Smart licenses for multichannel configurations. Requires XRadio Core module (not included) for audio library management and setting rules for music/advert scheduling. SOUNDTRACK STUDIO Radio automation software. Live Assist. Automatic audio selection and 720.00 playlist scheduling. Easy advertising scheduling. Jingle machines. Recorder. WEB streaming. Time signal. On Air WEB viewer for talents, showing real time info about playlist, artist and title.





| Model                          | Description   | UK List<br>ex VAT (£) |
|--------------------------------|---|-----------------------|
| Digital Audio Processors       |   | , ,                   |
| FALCON X5                      | FM/DAB+/HDRadio/WEB/DRM Digital Audio Processor 5 bands. 1RU. Analog, digital AES. 2x MPX out LCD display.  | 1,935.00              |
| FX-DANTE                       | Dante AoIP interface for Audio Processor Falcon X/D series. Support for AES67 RTP, SMPTE ST2110-30 RTP.   | 530.00                |
| FX-X5+                         | Upgrade from Falcon X5: Audio and MPX automatic changeover for Falcon X5 and audio streaming I/O.   | 880.00                |
| FX-X5-CHANGEOVER               | Audio and MPX automatic changeover for Falcon X5  | 355.00                |
| FX-TUNER                       | Tuner interface for Audio Processor Falcon X series.  | 270.00                |
| FALCON X7                      | FM/DAB+/HDRadio/WEB/DRM Digital Audio Processor 5 bands. 1RU. Analog, digital AES and streaming I/O. 2x MPX out. Audio and MPX changeover. SD slot to store files for backup device. LCD display.   | 2,805.00              |
| FALCON D7                      | TV/DAB+/HDRadio/WEB Digital Audio Processor 5 bands. 1RU. Loudness<br>Control ITU-1770. Analog, digital AES and streaming I/O. SD slot to store files<br>for audio backup. LCD display.   | 2,370.00              |
| FX-RDS                         | Digital RDS/RBDS encoder option for Falcon X. Dynamic services generation: 60 PS programmable messages for each DataSet. 2 interchangeable DataSet via remote control. RadioText, Alternative Frequency AF, Traffic Program TP, Traffic Announcement TA, EON, M/S, CT, PI, PTY, PIN. UECP SPB490 compliant.   | 355.00                |
| FM Broadcast Tuner             |   |                       |
| LYNX                           | Digital FM broadcast receiver. Balanced analog and digital AES/EBU audio output. Audio streaming. Dual LAN/USB. Headphone output on front panel. Universal power supply.  | 890.00                |
| FM Off-Air Monitoring And Stre |   |                       |
| WOLF 2MS                       | Dual FM monitoring system for FM networks. Double internal tuner with configurable band scan. Real time measures on RF, MPX, Audio and RDS decoder with group sequence. HTTP, SNMP, FTP and XML protocol. Web server, double audio streaming for monitor. 2xLAN/USB and GPIO. Headphone output. Universal PSU | 1,675.00              |
| WOLF 1MS                       | Monitoring system for FM networks. Internal FM tuner with configurable band scan. Real time measures on RF, MPX, Audio and RDS decoder with group sequence. HTTP, SNMP, FTP and XML protocol. Web server and audio streaming for monitor. 2xLAN/USB and GPIO. Headphone output and universal power supply.    | 1,415.00              |
| FM Re-Broadcast Receiver       |   |                       |
| PUMA                           | FM Re-Broadcast receiver tuner with MPX Output. Real time measures on RF, MPX, Audio and RDS decoder with group sequence. HTTP, SNMP, FTP and XML protocol. Web server and audio streaming for monitor. Trap and email alarm. 2x LAN/USB and GPIO. Headphone output and universal power supply.               | 1,585.00              |





| Model                          | Description   | UK List<br>ex VAT (£) |
|--------------------------------|---|-----------------------|
| Audio Logger                   |   |                       |
| DML-A-1CH                      | Software licence Digital Audio Logger: 1 audio channel digital recorder; MP3 audio encoding; includes Player and Monitor software utility   | 490.00                |
| DML-A-4CH                      | Software licence Digital Audio Logger: 4 channels audio digital recorder; MP3audio encoding; incldes Player and Monitor software utility  | 970.00                |
| DML-A-8CH                      | Software licence Digital Audio Logger: 8 channels audio digital recorder; MP3audio encoding; incldes Player and Monitor software utility  | 1,750.00              |
| RDS encoder                    |   |                       |
| RDS E3                         | Digital RDS/RBDS codec. n. 8 Dataset. UECP v.7.05. ODA, TMC, IH, RT, RT+. Scheduler PS, RT, PTY. Ethernet, Web server for encoder setup, SNMP v2.0. 6 GPI, 4 Relays. Radio automation interface. GPS.   | 1,240.00              |
| RDS E5                         | Digital RDS/RBDS codec. n. 8 Dataset. UECP v.7.05. ODA, TMC, IH, RT, RT+. Scheduler PS, RT, PTY. Ethernet, Web server for encoder setup, SNMP v2.0. 6 GPI, 4 Relays. Radio automation interface. GPS. 480x128 full color TFT display for visualization and parameters setup.                          | 1,415.00              |
| RDS encoder & Stereo Generator |   |                       |
| TIGER-SYNCH-STREAM             | Synchronized audio streaming module for Tiger E3/E5   | 370.00                |
| TIGER-TUNER                    | Tuner option for TIGER E3 and TIGER E5  | 270.00                |
| TIGER-MULTIMEDIA               | Multimedia option for TIGER E3: Streaming IN, Streaming OUT, Media player   | 355.00                |
| TIGER E3                       | Digital MPX+RDS coder with analog/digital/MPX inputs. Audio & MPX Changeover. RDS with n.8 Dataset. UECP v.7.05. ODA, TMC, IH, RT, RT+. Scheduler PS, RT, PTY. Web Server, SNMP v2.0. 6 GPI, 4 Relays. Radio automation interface. GPS. Streaming I/O available as option.                            | 1,585.00              |
| TIGER-DIGITAL MPX IO           | Digital AESEBU MPX input output 192KHz.   | 270.00                |
| TIGER E5                       | Digital MPX+RDS coder with analog/digital/MPX inputs. Streaming IN/OUT. Media Player. Audio & MPX Changeover. RDS with n.8 Dataset. UECP v.7.05. ODA, TMC, IH, RT, RT+. Scheduler PS, RT, PTY. Web Server, SNMP v2.0. 6 GPI, 4 Relays. Radio automation interface. GPS. Display TFT Hi-Res.           | 1,760.00              |
| TIGER E5 ENCODER               | Digital MPX+RDS coder with analog/digital/MPX inputs. Synchronized Streaming OUT. Media Player. Audio & MPX Changeover. RDS with n.8 Dataset. UECP v.7.05. ODA, TMC, IH, RT, RT+. Scheduler PS, RT, PTY. Web Server, SNMP v2.0. 6 GPI, 4 Relays. Radio automation interface. GPS. Display TFT Hi-Res. | 2,105.00              |





| Model                          | Description  | UK List<br>ex VAT (£) |
|--------------------------------|--|-----------------------|
| Signalling Studio Lamp         |  |                       |
| MRLIGHT-LPWS                   | Power supply powering up to 3 Lamps (Led) 110/220VAC for Mr. Light L/LD, separate light up and blinking feature management. Total power 10W 12V  | 125.00                |
| MRLIGHT RGB 2                  | Mr Light RGB On-Air (Led) lamp, multi-coloured RGB leds. Operating mode: blink, pulse. Wi-Fi and GPIs for remote control. Low power consumption. 12Vdc PSU and mounting kit included.  | 285.00                |
| Switcher, Changeover & Distrib |  |                       |
| FOX3-DANTE                     | Dante option for FOX 3   | 545.00                |
| FOX3-TUNER                     | FM Tuner module for FOX 3  | 285.00                |
| FOX3-MPX                       | Digital silence detector, failover audio switcher and converter; inputs: 1 analog, 2 digital AES/EBU, 2 IP, 2 MPX; outputs: 1 analog, 2 digital AES/EBU, 1 IP. USB port, built-in media player as back-up source. GPI I/O. 1RU. Universal PSU. AGC, SNMP, WEB GUI. | 1,500.00              |
| Telephone Hybrid               |  |                       |
| MACROTEL X1 MULTIMODE          | Digital telephone hybrid, 1 line POTS/BlueTooth/VOIP. DSP audio process, balanced IN/OUT XLR. RX/TX levels display. Web Server. Optional GSM module. GPI and GPO. Rack 19" 1u.   | 850.00                |
| MACROTEL X2 MULTIMODE          | Digital telephone hybrid, 2 lines POTS/BlueTooth/VOIP. DSP audio process, balanced IN/OUT XLR. RX/TX levels display. Web Server. Optional GSM modules. GPI and GPO. Rack 19" 1u.   | 1,325.00              |
| MCRX-DIGITAL  Time Display     | Digital audio AES/EBU input/output for Macrotel X Multimode  | 250.00                |
| ON AIR CLOCK                   | On Air Clock Broadcast Display - Software licence for studio clock with timer, count up, count down, logo, etc. Includes: OAC Software License, Windows MiniPC, HDMI output (monitor not included).  | 635.00                |
| Time Synchronizer              | This of the industry individuals.  |                       |
| STS                            | Sat Time Synchronizer software (client/server for LAN networks) PC time  | 460.00                |

synchronization with sat GPS receiver. 10m serial cable included