



Live-Link™ Remote Camera Interface System Feature-by-Feature Comparison Chart

Live-Link Version	Live-Link Mini		Live-Link Jr.	"04X" Series		"05X" Series	"06X" Series	"07X" Series
Camera End Unit	LLM-CA-105		LLJR-CA-101/105	LL-3G-CA-041/045		LL-3G-CA-051/055	LL-3G-CA-061/065	LL-3G-CA-075/076
Truck End Unit / Control Room Unit	LLM-TE-107	LLM-TE-109	LLJR-TE-101	LL-3G-CR-041/042/ 045/046	LL-3G-CR-043/044/ 047/048	LL-3G-CR- 051/052/055/056	LL-3G-CR- 061/062/065/066	LL-3G-CR-075/076
Digital Video Paths (3G/HD/SD-SDI)								
Camera End to Truck End / Control Room	1		1	2		3	2	5
Truck End / Control Room to Camera End	1	1	1	2		2	2	1
Analog Video Paths (NTSC/PAL)								
Control Room to Camera End							1 (Tru-Sync™ technology)	
Mic/Line Inputs (Camera End)			2	4		4	4	4
Mic/Line Outputs (Truck End / Control Room)			2	4		4	4	4
De-Embed Audio Outputs (Truck End)	4	2	2					
Line/IFB Returns (Camera End)								
Line Outputs	2		2	2		2	2	2
IFB Outputs (powered)	1		1	1		1	1	1
Party-Line Intercom (Camera End)	• (powered, on/off selectable)		• (powered)	• (powered)		• (powered)	• (powered)	• (powered)
Party-Line Intercom (Truck End)	• (powered, on/off selectable)		• (powered, on/off selectable)	• (powered, on/off selectable)				
4-Wire Intercom (Truck End / Control Room)	• (1 channel)		• (1 channel)	• (2 channels)		• (2 channels)	• (2 channels)	• (2 channels)
Ethernet Transport								
Async Data Transport			1 (RS-422)	1 (RS-422), 1 (RS-232)		1 (RS-422), 1 (RS-232)	1 (RS-422), 1 (RS-232)	1 (RS-422), 1 (RS-232)
Contact Closures (GPI/GPO)			1	2		2	2	2
Optical Fibers (Single Mode)	1		2	2		2	2	2
Optical Connectors (Camera End)	1 ST		opticalCON® DUO, 2 ST, or 1 ST	opticalCON DUO or 2 ST		opticalCON DUO or 2 ST	opticalCON DUO or 2 ST	2 ST
Optical Connectors (Truck End / Control Room)	1 ST		2 ST or 1 ST	opticalCON DUO or 2 ST		opticalCON DUO or 2 ST	opticalCON DUO or 2 ST	2 ST
Enclosure Type								
Camera End	Portable		Portable	Portable		Portable	Portable	Portable or Rack-Ready
Truck End / Control Room	Rack-Mount	Portable	Rack-Mount	Portable or Rack-Ready		Portable or Rack-Ready	Portable or Rack-Ready	Portable or Rack-Ready
Camera End Power								
Battery (Anton/Bauer® standard, V-mount optional)	•		•	•		•	•	• (Portable only)
10-18 Vdc (external power supply included)	•		•	•		•	•	•
10-50 V (using hybrid/fiber cable)			•	Optional		Optional	Optional	
Truck End / Control Room Power								
Battery (Anton/Bauer standard, V-mount optional)			•	• (Portable only)		• (Portable only)	• (Portable only)	• (Portable only)
10-18 Vdc (external power supply included)	•		•	•		•	•	•
100-240 V, 50/60 Hz	•		•					