

Multi-track technology for the 21st century

BLACKBOX BBR64-MADI RECORDER

Designed for a range of applications including Live Music, Broadcast, Film & TV Sound - in fact just about anything that requires the capture of multiple channels of live audio material with minimum fuss.



64 channels in one rack unit

The JoeCo **BLACKBOX BBR64-MADI RECORDER** is based on the award-winning, tried and tested **BlackBox Recorder** design. However, rather than being limited to recording 24 channels of audio, the **BBR64-MADI** is designed to record and replay up to 64 channels of MADI data.

Developed to solve the inherent problems of working with computer-based systems in a live performance environment, the **BlackBox Recorder** provides engineers with a computer-free, high-quality solution for multi-channel live audio capture. The **BlackBox BBR64-MADI Recorder** can capture the full 64 channels of MADI data at standard sample rates directly to Broadcast WAV files on an external USB2 drive, and yet only occupies one unit of rack space! Double sample rate MADI recording (up to 96kHz) is also accommodated.

The recorder sports both coaxial and optical MADI connections for interfacing with any MADI equipped console or other equipment. Additionally, the **BBR64-MADI** caters for 56-channel legacy MADI and can record a further 8 channels of analogue (balanced line in) for capturing the audience reaction or general ambience.

The **BBR64-MADI** will lock to or generate word clock, as well as locking to the received MADI data stream. The MADI input can be echoed direct to the output to ease system integration. Individual channels or pairs of channels can be monitored on an internal PFL bus providing both hi-resolution metering and headphone output.

The recorder is designed to be supremely simple to use, requiring just the input and output connections, power and a USB drive before pressing the RECORD button. A full colour LCD screen and striking LED displays show all the information the recording engineer needs in order to know what's happening.

The **BBR64-MADI** includes numerous safety features, inherited from the original **BlackBox Recorder**, to keep your recording as secure as possible. Safe'n'Sound Record Recovery will recover files even if the power fails in the middle of a recording.

- 64-channel record or playback at 44.1kHz and 48kHz.
- Only 1 rack unit tall (435 x 44 x 170mm) and weighing just 2.1kg.
- Records standard broadcast WAV files to an external USB2 drive. Captured audio material can be imported into any digital workstation for instant re-purposing. No file transfer necessary.
- Simple to operate and understand.
- Simple to see what's going on to disk.
- PFL bus for monitoring individual / pairs of channels, providing both hi-resolution metering and headphone monitoring.
- Safe'n'Sound Record Recovery protects your files in case of power failure.
- Files can be time-stamped with respect to incoming timecode.
- Track, Song and Folder naming.
- Remote control via QWERTY keyboard, MIDI, Sony 9-pin.
- Multiple units can be stacked for larger track counts.

Technical Specifications:

General

Sample rates:	44.1kHz, 48kHz, (88.2kHz, 96kHz at reduced track count)
Bit depths:	16 / 24bit
Disk interface:	USB2 - easy to obtain
Disk Format:	FAT32 - compatible with both Mac and PC
File format:	Broadcast Wave (BWA) - universally readable
External drive:	1 off USB2 (480Mbit/sec); BBR64-MADI writes 9.5Mbytes/sec for 64ch@48k = 33.4Gbytes/hour (10,000rpm drives recommended to optimise seek times during playback). Supports USB2 RAID arrays (such as the Glyph or Drobo devices).
File type:	Standard mono Broadcast WAV files
Monitoring:	Headphone output provides mono or dual mono pre fade listen (PFL) of any channel with hi-res metering
Physical:	Size: 19" rack mounting x 1U (435 x 44 x 170mm) Weight: < 2.1kg DC input: 9-12V dc (PSU supplied) Power: < 25W

Audio i/o

Record / playback:	<ul style="list-style-type: none"> • 64ch record or playback @ 44.1kHz and 48kHz • Supports both coaxial and optical variants of MADI data • Supports 56ch MADI (and passes through the DiGiCo ch57 mic amp control data as well) • 88.2kHz and 96kHz (double sample rate, SMUX & normal) recording also supported (but at half the track count)
Inputs:	Coaxial and optical (SC) MADI support, Word clock, 8ch balanced analogue line inputs
Outputs:	Coaxial and optical (SC) MADI support, word clock output, headphones

Control and Synchronisation

Audio clock synchronisation:	Lock to incoming MADI audio stream or separate word clock. Can also generate word clock
Control:	QWERTY keyboard, MIDI, Sony 9-pin, GPI contact closure

BBR64-MADI Rear Panel



BBR64-MADI Distributed by:

**JoeCo Limited, 135 Histon Road,
Cottenham, Cambridge, CB24 8UQ, UK**

Registered in England: 6361413 VAT Number: GB 923 8706 10. All rights reserved. Any trademarks and intellectual property rights are acknowledged as the property of their respective owners. JoeCo Ltd reserves the right to make changes to specifications at any time and without prior notice. E&OE etc.